

CONCRETE PAVING  
 SAWCUT PATTERN 500 x 500 x 5mm  
 STIPPLE FINISH  
 COLOURED "COLORMIX SILVER" @ 10kg/m<sup>3</sup>

PEDESTRIAN CROSSING  
 -REFER TO LCC 402 & 403

LONGITUDINAL JOINT TYPE 1

**NOTES**

- FOOTPATH PAVEMENT AS PER SPECIFICATION
- ISOLATION JOINTS TO BE PLACED AT PROPERTY LINE AND BACK OF KERB
- EXPANSION JOINTS AT 12 m CENTRES PERPENDICULAR TO PROPERTY LINE
- ISOLATION JOINTS TO BE PLACED AROUND ALL MAJOR FIXED STRUCTURES SUCH AS DRAINAGE AND OTHER SERVICE PITS
- PATTERN IN PAVING TO BE SAWCUT TO GIVE A NEAT GROOVE 7 mm MIN. DEPTH, 3 mm WIDE
- SET OUT PATTERN FROM BACK OF KERB TOWARDS PROPERTY LINE OR FROM OTHER NOMINATED CONTROL
- DO NOT SAWCUT SERVICE PITS

TYPICAL PLACEMENT OF EXPANSION JOINT (REFER LCC 412)



GENERAL NOTES / CROSS REFERENCES

1. All dimensions in mm unless otherwise noted.
2. Concrete strength as per specification.


File name: LCC 411 Concrete CBD paving.pro

# Latrobe City

## CONCRETE PAVING CBD AREAS

CITY AUTHORISATION

VERSION/  
 DATE OF PLOT 1/4/2015



DWG No. **LCC 411**

SHEET NO. **1** OF **1**